

LIGHT TRUCK TYRES

Only apply EQUAL in light commercial tyre sizes, clearly marked "C" or "LT"

Tyre size		SINGLE fitment	DUAL fitment
195/70	R 15	F	F
6.50	R 16	F	F
7.50	R 16	F	F
8.25	R 16	F	F
205/55	R 16	F	F
195/60	R 16	F	F
205/60	R 16	F	F
215/60	R 16	F	F
225/60	R 16	F	F
195/65	R 16	F	F
205/65	R 16	F	F
215/65	R 16	F	F
225/65	R 16	F	F
235/65	R 16	E	E
305/65	R 16	D	D

Tyre size		SINGLE fitment	DUAL fitment
345/65	R 16	C	C
175/75	R 16	F	F
185/75	R 16	F	F
195/75	R 16	F	F
205/75	R 16	F	F
215/75	R 16	F	F
225/75	R 16	F	F
235/75	R 16	E	E
245/75	R 16	E	E
265/75	R 16	E	E
285/75	R 16	D	D
295/75	R 16	D	D
315/75	R 16	C	C
215/85	R 16	F	F
225/85	R 16	E	E
235/85	R 16	E	E

Tyre size		SINGLE fitment	DUAL fitment
245/85	R 16	E	E
255/85	R 16	D	D
265/85	R 16	D	D
305/85	R 16	C	C
225/55	R 17	F	F
255/55	R 17	F	F
215/60	R 17	F	F
245/70	R 17	E	E
265/70	R 17	E	E
275/70	R 17	E	E
285/70	R 17	D	D
315/70	R 17	D	D
245/75	R 17	E	E
235/80	R 17	E	E
275/65	R 18	D	D
245/70	R 18	D	D

TRUCK TYRES

Tyre size		SINGLE fitment	DUAL fitment
7.50	R 15	F	F
8	R 17.5	E	E
8,5	R 17.5	E	E
9	R 17.5	D	D
9,5	R 17.5	D	D
10	R 17.5	C	C
205/65	R 17.5	E	E
245/70	R 17.5	E	E
265/70	R 17.5	D	D
315/70	R 17.5	C	C
215/75	R 17.5	E	E
225/75	R 17.5	E	E
235/75	R 17.5	D	E
245/75	R 17.5	D	D
315/80	R 17.5	B	B
445/45	R 19.5	A	
435/50	R 19.5	A	
265/55	R 19.5	C	
385/55	R 19.5	A	
425/55	R 19.5	B	
255/60	R 19.5	D	D
385/65	R 19.5	A	
445/65	R 19.5	B + E	
225/70	R 19.5	D	C
245/70	R 19.5	D	C
265/70	R 19.5	D	C
285/70	R 19.5	C	B
295/70	R 19.5	C	B

Tyre size		SINGLE fitment	DUAL fitment
305/70	R 19.5	B	A
315/70	R 19.5	B	A
8.25	R 20	C	B
9.0	R 20	B	B
10.00	R 20	B	A
11.00	R 20	A	A
12.00	R 20	A	A
14.00	R 20	A + E	
16.00	R 20	A + D	
405/70	R 20	A + E	
375/75	R 20	A + E	
425/75	R 20	A + D	
275/80	R 20	B	A
335/80	R 20	A	
365/80	R 20	A	
475/80	R 20	A + A	
365/85	R 20	A + E	
395/85	R 20	A + D	
24	R 20.5	A + D	
10	R 22.5	B	A
11	R 22.5	B	A
12	R 22.5	A	A
13	R 22.5	A	A
445/40	R 22.5	C + D	
455/40	R 22.5	C + D	
315/45	R 22.5	B	A
435/45	R 22.5	B + E	
445/45	R 22.5	B + E	

Tyre size		SINGLE fitment	DUAL fitment
455/45	R 22.5	B + E	
495/45	R 22.5	A + D	
355/50	R 22.5	A	
375/50	R 22.5	A	
435/50	R 22.5	A + E	
445/50	R 22.5	A + E	
455/50	R 22.5	A + E	
295/55	R 22.5	B	A
385/55	R 22.5	A	
295/60	R 22.5	B	A
315/60	R 22.5	B	A
385/65	R 22.5	A (normal) A+E (heavy duty)	
425/65	R 22.5	A + D	
445/65	R 22.5	A + D	
255/70	R 22.5	C	B
275/70	R 22.5	B	A
305/70	R 22.5	B	A
315/70	R 22.5	B	A
365/70	R 22.5	C + D	
445/75	R 22.5	B + B	
255/80	R 22.5	C	B
275/80	R 22.5	B	A
295/80	R 22.5	A	A
315/80	R 22.5	A	A
375/90	R 22.5	B + C	
12.00	R 24	A	
325/95	R 24	C + D	
11	R 24.5	A	

July 2013

If the tyre size you are looking for is not listed in this chart, please contact REMA TIP TOP or www.equalchart.com

A = 12 oz (340g); B = 10 oz (280g); C = 8 oz (230g); D = 6 oz (170g); E = 4 oz (115g); F = 3 z (85g)